Technical Datasheet

nerbe plus GERMANY

EN ISO 13485 certified

		EN ISO 13485 certified
Article - No:	**09-312-0000**	**Revision: 2**
Remarks	**max. vol.: approx. 11 l / working vol.: approx. 5 l**	**single use only**

Specification

Product	Autoclavable bag PP, 300x500 mm, thickness: 50µm, natural, autoclavable up to 134°C
Dimensions	width: 300,00 mm (+/- 8 mm)
	length: 500,00 mm (-10/+20 mm)
	thickness: 50 µm (+/- 10%)
Colour	natural
Material Characteristics	polypropylene (PP)
Autoclavability	autocl. up to 134°C
Product Characteristics	biologically inert
	physiologically harmless
	extremely resilient double bottom seam
	density approx. 0,90 gr.
Packaging	pcs per cs: 1.000
	pcs per carton: 1.000
	pcs per pallet: 20.000
Storage	dry condition: 40%-60% rel. humidity
	bags / cases orig. closed
	storage temp. +10°C to max. +30°C
	pal. not stackable
Approved by nerbe plus quality department	

nerbe plus GmbH & Co. KG
Porschestr. 25
D-21423 Winsen/Luhe
Tel: +49 (0)4171 7849 0
Fax:+49 (0)4171 6 45 45

info@nerbe-plus.de
www.nerbe-plus.de
HRA Lüneburg 203240
USt.-ID: DE 32583 0652

Pers. haftende Gesellschafterin:
NERBE R&D GmbH, Winsen/Luhe
GF: Philipp J.F. Nerbe
HRB Lüneburg 208826

Deutsche Bank AG
Kto. 0204 41200
IBAN: DE41 2407 0075 0020 4412 00
SWIFT / BIC DEUTDE2H240

Hamburger Sparkasse
Kto. 1387 140831
IBAN: DE56 2005 0550 1387 1408 31
SWIFT / BIC HASPDEHHXXX

AEO