


SuperLift ø267 mm 10,8 ltr


Logical no: 8106
Available lids: 4083 (standard), 4086 (standard), 4108 (membrane)

Volume

Volume under lid: 10,8 ltr +/- 110 ml **Volume brimful:** 11,2 ltr +/- 110 ml

Dimensions

Shape: Round Conical
External dia top without lid: 269 mm +/- 3 mm **External diameter bottom:** 228,5 mm +/- 2 mm
External dia top with lid: 269 mm +/- 3 mm **Height without lid:** 249,8 mm +/- 2 mm
Height with std lid: 251 mm +/- 3 mm

Weight

Weight container/pot: 255 g +/- 8 g **Weight plastic handle:** 11 g +/- 2 g
Weight standard lid: 65 g +/- 4 g **Weight metal handle:** 31 g +/- 4 g

Stacking specifications

Stackability - dynamic: Max: 0 kg Max top load on bottom container at 23° **UN approval:** No
Stackability - static: Max: kg Max top load on bottom container at 23°
Stacking tests: The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.

Closure system

Lid type options: Standard lid, Optional membrane lid
Closure type: Peel-off
Protective collar: Yes
Tamper Evidence type: Break-out

Handle

Handle available: Flexible plastic on collar

Decoration

Decoration available: Dry Offset, Optional Dry Offset with lacquer **Decoration area offset:** 750x190 mm without overlap

Packing

On pallet 1200x800: 468 pcs. **On pallet :** NA pcs.
Pieces per layer: 13 pcs. **Pieces per layer:** NA pcs.
Height incl. pallet: 1,26 m **Height incl. pallet:** NA m
Stackability, empty: 2 pallets high **Stackability, empty:** NA pallets high

Raw material

Raw material options:

PP



Masterbatch colours: Colours according to Superfos standard selected pantone colours.

Hot filling:

Hot temperatures:

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures

Special:

Cold temperatures:

Freezing conditions require special resins available on request. The Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures

Quality Specifications

Approvals: All Superfos Products comply with the European legislation 2002/72 with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun

light, rain, very low temperatures or very high temperatures over a long period

Quality information:

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

Specifications are subject to change without notice.

Version 10.1

Latest revision : 19-01-2011